

4





3

2

GENERAL TOLERANCE							
DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400	SURFACE FINISH	
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5	1.6	

CUSTOMER DRAWING

REVISIONS			
REV	DESCRIPTION	DATE	
A	First release	2020-05-06	



- NOTES:
- THE PRODUCTS ARE ROHS COMPLIANCE.
 - MATERIAL SPEC: PA THERMOPLASTIC,UL94 V-0,BLACK COLOR..

UNLESS OTHERWISE SPECIFIED		SPECIFICATIONS		POS	QTY	PART NUMBER	DESCRIPTION	NOTE	
LINEAR DIMENSIONS ARE IN: MILLIMETERS TOLERANCES: ANGLES: ±2° DEFAULT LINEAR TOLERANCES SEE TABLE DIM. & TOL. PER ASME Y14.5M-1994; DRM PER MIL-DTL-31000;		MATERIAL SPEC.		APPROVALS		DATE	上海良速电子有限公司 Powermax 28pin dual row Female connector U		
		SEE NOTES 2		PREPARED BY	JUSTIN LI	2020/5/6			
		PROCESS SPEC.		ENGINEER IN CHARGE					TYLER QIU
				DESIGN MANAGER					TYLER QIU
				DESIGN ACTIVITY GROUP					THIRD ANGLE PROJECTION
LEGENDS: =FLAG NOTE CALL OUT REFERENCE ONLY		--				SCALE:	REF.	SHEET 1 OF 1	

A

B

C

D

4

3

2

1